

## OT 130/220...240/24 DIM P

CV Power supplies 24 V with 1...10 V



### Product family features

- DC mode functionality
- Type of protection: IP66 and IP67
- Surge protection: up to 4 kV (L-N) / 6 kV (L/N-PE)
- Wide operating temperature range: -30...+55 °C
- Lifetime: up to 50,000 h (temperature at max.  $t_c$ )
- Dimmable via fully isolated 1...10 V interface

### Product family benefits

- Large range of products from 20 W to 250 W
- Installation in very cold and hot environments
- Very stable output power
- High electrical reversible short-circuit, overload, overtemperature protection
- Smart Power Supply: boosting power to turn on cold LEDs
- Independent installation possible
- Dimming range: 1...100 %

### Areas of application

- Facades, public squares, cruise ships
- Signage
- Suitable for indoor and outdoor installations

# Product datasheet


## Technical data

### Electrical data

Nominal output power	130 W
Maximum output power	130 W
Mains frequency	0...60 Hz
Efficiency in full-load	90.5 % <sup>1)</sup>
Galvanic isolation primary/secondary	3 kV
Nominal output voltage	24.2 V
Input voltage DC	176...276 V
Input voltage AC	198...264 V

<sup>1)</sup> at 230 V, 50 Hz

### Dimensions & weight



Mounting hole spacing, length	207.0 mm
Product weight	943.00 g
Length	220.0 mm
Width	63.0 mm
Height	37.0 mm

### Temperatures & operating conditions

Permitted rel. humidity during operation	5...85 % <sup>1)</sup>
--	------------------------

<sup>1)</sup> Maximum 56 days/year at 85 %

### Capabilities

Suitable for fixtures with prot. class	I
Overheating protection	Yes
Overload protection	Yes
Short-circuit protection	Yes

## Product datasheet

No-load proof	Yes
Intended for no-load operation	No
Dimming interface	1...10 V
Dimmable	Yes
Number of channels	1












### Certificates & standards

Type of protection	IP66/IP67
Standards	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 61000-3-3/Acc. to EN 60598-1/Acc. to EN 62384
Approval marks – approval	ENEC / RCM / CCC / EAC

### Logistical data

Commodity code	850440829000
----------------	--------------

### Download Data

File
 User instruction OPTOTRONIC LED Power Supply
 Addon Technical Information Dimming table for OT (EN)
 Product Datasheet Datasheet OT 130220-24024 DIM P
 Brochures OPTOTRONIC constant-voltage LED power supplies and controls (EN)
 Certificates CCC Certificate No. 2018011002043871
 Certificates CB Test Certificate No. SG PSB-LE-00906
 Certificates ENEC Certificate No. U6 18 01 84117 048
 Declarations of conformity EU Declaration of Conformity 3537796
 Declarations of conformity Attestation of Conformity No. N8A 18 01 84117 054
 Declarations of conformity Attestation of Conformity No. E8A 18 01 84117 049
 Declarations of conformity EU Declaration of Conformity OT 24V P_DIMP

## Product datasheet

---

### Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899545885	OT 130/220...240/24 DIM P	Shipping carton box 10	439 mm x 299 mm x 126 mm	16.54 dm <sup>3</sup>	10590.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.