

General Purpose Aluminium Electrolytic Capacitors 105°C

multicomp PRO



Features:

- For general purpose
- Wide CV value range
- Safely vent construction products, RH series are guaranteed 2,000 hours at 105°C

Specifications

No.	Item	Performance																																																										
1	Operating Temperature Range	-40°C to +105°C	-25°C to +105°C																																																									
2	Rated Working Voltage Range	6.3 - 100V DC	160 - 450V DC																																																									
3	Nominal Capacitance Range	0.1 - 15,000µF	0.47- 330µF																																																									
4	Capacitance Tolerance	± 20% (at +20°C ,120Hz)																																																										
5	Leakage Current	$I \leq 0.01CV$ or $3(\mu A)$ max.	$I \leq 0.03CV$ or $20(\mu A)$ max.																																																									
		Whichever is greater after 3 minutes	I: Leakage Current (μA) C: Rated Capacitance (μF) V: Working Voltage (V)																																																									
6	Dissipation Factor ($\tan \delta$) (120Hz\+20°C)	<table border="1"> <thead> <tr> <th>Working Voltage</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>100</th> <th>160</th> <th>200</th> <th>250</th> <th>350</th> <th>400</th> <th>450</th> </tr> </thead> <tbody> <tr> <td>$\tan \delta$ max.</td> <td>0.22</td> <td>0.19</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.1</td> <td>0.1</td> <td>0.07</td> <td>0.15</td> <td>0.15</td> <td>0.15</td> <td>0.2</td> <td>0.24</td> <td>0.24</td> </tr> </tbody> </table>												Working Voltage	6.3	10	16	25	35	50	63	100	160	200	250	350	400	450	$\tan \delta$ max.	0.22	0.19	0.16	0.14	0.12	0.1	0.1	0.07	0.15	0.15	0.15	0.2	0.24	0.24																	
		Working Voltage	6.3	10	16	25	35	50	63	100	160	200	250	350	400	450																																												
$\tan \delta$ max.	0.22	0.19	0.16	0.14	0.12	0.1	0.1	0.07	0.15	0.15	0.15	0.2	0.24	0.24																																														
		Add 0.02 per 1,000 µF for more than 1,000µF																																																										
7	Maximum Permissible Ripple Current	Refer to standard products table (120Hz, +105°C) Correction factor for frequency																																																										
		Freq.(Hz)		60	120	1K	10K	100K																																																				
		W. V. (V. DC.)																																																										
		6.3-50	0.1-330	0.85	1	1.3	1.4	1.55																																																				
			470-3300	0.95	1	1.15	1.2	1.25																																																				
			≥4700	0.95	1	1.1	1.2	1.2																																																				
63-100	0.47-33	0.75	1	1.55	1.65	1.8																																																						
	47-220	0.75	1	1.4	1.6	1.65																																																						
	≥330	0.8	1	1.3	1.35	1.4																																																						
≥160	1-220	0.7	1	1.3	1.7	1.7																																																						
8	Characteristics at low temperature (stability at 120 Hz)	<table border="1"> <thead> <tr> <th>Working Voltage</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>100</th> <th>160</th> <th>200</th> <th>250</th> <th>350</th> <th>400</th> <th>450</th> </tr> </thead> <tbody> <tr> <td>-25°C/+20°C</td> <td>4</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>3</td> <td>3</td> <td>3</td> <td>6</td> <td>6</td> <td>15</td> </tr> <tr> <td>-40°C/+20°C</td> <td>8</td> <td>6</td> <td>4</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>														Working Voltage	6.3	10	16	25	35	50	63	100	160	200	250	350	400	450	-25°C/+20°C	4	3	2	2	2	2	2	2	3	3	3	6	6	15	-40°C/+20°C	8	6	4	3	3	3	3	3	-	-	-	-	-	-
		Working Voltage	6.3	10	16	25	35	50	63	100	160	200	250	350	400	450																																												
		-25°C/+20°C	4	3	2	2	2	2	2	2	3	3	3	6	6	15																																												
-40°C/+20°C	8	6	4	3	3	3	3	3	-	-	-	-	-	-																																														
		For capacitance value >1,000 µF, Add 0.5 per another 1,000 µF for -25°C/+25°C. Add 1 per another 1,000µF for -40°C/+20°C																																																										

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO

General Purpose Aluminium Electrolytic Capacitors 105°C



No.	Item	Performance	
9	High Temperature Loading	After 2,000 hrs. application of DC rated working voltage at +105°C, The capacitor shall meet the following limits: Post test requirements at +20°C	
		Leakage current	≤ the initial specified value
		Capacitance change	≤ ±20% of initial measured value
		Dissipation Factor(tan δ)	≤ 200% of initial specified value
10	Shelf Life	After storage for 500hrs. at +105°C with no voltage applied. Post test requirements at +20°C same limits as high temperature loading.	

Permissible Ripple Current

W.V(SV)	6.3	10	16	25	35	50	63	100	160	200	250	350	400	450
μ F	(8)	(13)	(20)	(32)	(44)	(63)	(79)	(125)	(200)	(250)	(300)	(400)	(450)	(500)
0.1	-	-	-	-	-	7	-	8	8	8	8	9	9	10
0.22	-	-	-	-	-	7	-	8	8	8	8	9	9	10
0.33	-	-	-	-	-	7	-	8	8	8	8	9	9	10
0.47	-	-	-	-	-	8	-	10	9	9	9	10	9	18
1	-	-	-	-	-	12	-	15	12	12	12	18	18	18
2.2	-	-	-	-	-	17	-	23	19	19	21	30	30	30
3.3	-	-	-	-	-	21	-	29	26	26	30	37	40	43
4.7	-	-	-	26	28	30	32	34	31	36	36	48	52	56
10	-	-	35	38	41	46	50	56	59	59	64	79	79	79
22	-	49	54	57	61	68	82	96	95	95	110	130	145	150
33	54	60	64	69	75	90	100	140	125	140	140	175	185	190
47	65	70	99	82	100	110	135	180	165	165	180	230	230	-
100	95	105	125	135	170	180	223	320	270	285	310	350	-	-
220	160	175	215	230	300	345	400	570	450	550	-	-	-	-
330	195	245	260	335	400	460	540	700	850	-	-	-	-	-
470	270	290	370	440	520	610	700	880	-	-	-	-	-	-
1,000	460	550	640	770	920	1,080	1,210	-	-	-	-	-	-	-
2,200	810	860	1000	1,170	1,340	1,530	-	-	-	-	-	-	-	-
3,300	960	1,100	1,300	1,460	1,650	1,850	-	-	-	-	-	-	-	-
4,700	1,330	1,400	1,600	1,780	1,900	-	-	-	-	-	-	-	-	-
6,800	1,500	1,690	1,900	1,950	-	-	-	-	-	-	-	-	-	-
10,000	1,765	1,950	2,000	-	-	-	-	-	-	-	-	-	-	-
15,000	2,075	2,100	-	-	-	-	-	-	-	-	-	-	-	-

General Purpose Aluminium Electrolytic Capacitors 105°C

multicomp PRO

Case Size Table

W.V. (SV)	6.3	10	16	25	35	50	63	100
µF	(8)	(13)	(20)	(32)	(44)	(63)	(79)	(125)
0.1	-	-	-	-	→	5 × 11	-	5 × 11
0.22	-	-	-	-	→	5 × 11	-	5 × 11
0.33	-	-	-	-	→	5 × 11	-	5 × 11
0.47	-	-	-	-	→	5 × 11	-	5 × 11
1	-	-	-	-	→	5 × 11	-	5 × 11
2.2	-	-	-	-	→	5 × 11	-	5 × 11
3.3	-	-	-	-	→	5 × 11	-	5 × 11
4.7	-	-	-	-	→	5 × 11	-	5 × 11
10	-	-	→	5 × 11	5 × 11	5 × 11	5 × 11	6.3 × 11
22	-	-	→	5 × 11	5 × 11	5 × 11	6.3 × 11	8 × 11
33	-	→	5 × 11	5 × 11	5 × 11	6.3 × 11	6.3 × 11	10 × 13
47	→	5 × 11	5 × 11	5 × 11	6.3 × 11	6.3 × 11	8 × 11	10 × 16
100	→	5 × 11	6.3 × 11	6.3 × 11	8 × 11	8 × 11	10 × 13	13 × 21
220	→	6.3 × 11	8 × 11	8 × 11	10 × 13	10 × 16	10 × 21	16 × 26
330	6.3 × 11	8 × 11	8 × 11	10 × 13	10 × 16	10 × 21	13 × 21	16 × 26
470	8 × 11	8 × 11	10 × 13	10 × 16	10 × 21	13 × 21	13 × 26	16 × 32
1,000	10 × 13	10 × 16	10 × 21	13 × 21	13 × 21	16 × 26	16 × 32	-
2,200	10 × 21	13 × 21	13 × 21	13 × 26	16 × 32	18 × 36	-	-
3,300	13 × 21	13 × 21	13 × 26	16 × 32	18 × 36	18 × 42	-	-
4,700	13 × 26	16 × 26	16 × 32	18 × 36	18 × 42	-	-	-
6,800	16 × 26	16 × 32	18 × 36	18 × 42	-	-	-	-
10000	16 × 32	18 × 36	18 × 42	-	-	-	-	-
15000	18 × 36	18 × 42	-	-	-	-	-	-

All blank voltage on sleeve marking is the same voltage as “→” point to.

Case Size Table

WW (SV)	160	200	250	350	400	450
µF	(200)	(250)	(300)	(400)	(450)	(500)
0.47	6.3 × 11	6.3 × 11	6.3 × 11	8 × 11	8 × 11	8 × 11
1	6.3 × 11	6.3 × 11	6.3 × 11	8 × 11	8 × 11	10 × 16
2.2	6.3 × 11	6.3 × 11	6.3 × 11	8 × 11	10 × 13	10 × 21
3.3	6.3 × 11	6.3 × 11	8 × 11	10 × 13	10 × 13	13 × 21
4.7	6.3 × 11	8 × 11	8 × 11	10 × 13	10 × 16	13 × 21
10	8 × 11	10 × 13	10 × 16	10 × 21	13 × 21	16 × 26

Dimensions : Millimetres

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro


multicomp PRO

General Purpose Aluminium Electrolytic Capacitors 105°C

multicomp PRO

WW (SV)	160	200	250	350	400	450
µF	(200)	(250)	(300)	(400)	(450)	(500)
22	10 × 16	10 × 21	13 × 21	13 × 26	13 × 26	16 × 32
33	10 × 21	13 × 21	13 × 21	16 × 26	16 × 32	18 × 32
47	13 × 21	13 × 21	13 × 26	16 × 36	18 × 36	-
100	13 × 26	16 × 26	16 × 32	18 × 42	-	-
220	16 × 36	18 × 42	-	-	-	-
330	18 × 42	-	-	-	-	-


Diagram of Dimensions



DØ (+0.5Max.)	5	6.3	8	10	13	16	18	22
F (±0.5)	2	2.5	3.5	5	5	7.5	7.5	10
dØ (±0.02)	0.5	0.5	0.6	0.6	0.6	0.8	0.8	0.8

Dimensions : Millimetres

Part Number Explanation



Voltage : 6.3V, 10V, 16V, 25V, 35V, 50V, 63V, 100V, 160V, 200V, 250V, 350V, 400V & 450V
 Capacitance : 336 = 33mH
 337 = 330mF
 338 = 3300mH

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO